



KEY FEATURES

H-Star technology for subfoot postprocessed accuracy

Optional Zephyr antenna for 8-inch postprocessed accuracy

Receiver, antenna and battery in one compact unit

Bluetooth wireless technology for convenient cable-free operation

Rugged and weatherproof for all conditions

User-replaceable battery that lasts a full day in the field

Choice of field device and field software to suit your workflow



HIGH PERFORMANCE INTEGRATED GPS RECEIVER FOR SUBFOOT ACCURACY

The GPS Pathfinder® ProXH™ receiver introduces a new era in GPS for GIS data collection. A GPS receiver, antenna, and all-day battery in one, the ProXH receiver delivers subfoot (30 cm) accuracy with Trimble's revolutionary H-Star™ technology. Don't be fooled by its rugged good looks—the ProXH receiver is quite simply the most sophisticated high performance GPS receiver on the market.

Introducing H-Star technology

Bringing together advanced GPS receiver design and a powerful new postprocessing engine, H-Star technology is in a class of its own. There's no need to initialize—in the time taken to record your attribute information, the ProXH receiver logs the data you need to achieve subfoot accuracy. And you can collect data with confidence; Trimble field software displays the accuracy you can expect after postprocessing, while you're in the field.

Back in the office, the GPS Pathfinder Office software, or the Trimble® GPS Analyst™ extension for ESRI ArcGIS software, guides you through the H-Star correction process and shows you the accuracy you've achieved.

Need to get the very best accuracy? Add a Zephyr™ antenna to your ProXH receiver to get 8 inch (20 cm) accuracy. H-Star technology is more than just a GPS receiver, it's a total system for high accuracy GIS data collection.

Cable-free convenience

The all-in-one design of the ProXH receiver means it's simple to set up and easy to use. Forget lost or tangled cables: with a Bluetooth® wireless connection you're cable free between the ProXH receiver and your field computer. Nothing to snag or break as you move through difficult terrain.

The flexible mounting system makes it quick and easy to fit the ProXH receiver

for the job at hand. It all adds up to a powerful GPS system that maximizes your productivity and makes your fieldwork surprisingly simple.

All day every day

The receiver has an integrated battery, good for a full day's work; simply charge the battery overnight and you're ready to go again. The ProXH receiver will last the distance, and its rugged design can take a lot of punishment. Rain, hail or shine, it's built to keep working, whatever the environment throws at you.

Options to suit your workflow

You can choose a field computer and software to suit your workflow. The ProXH receiver is ready to use with a variety of field computers, including laptops, Tablet PCs and PDAs, and of course Trimble's own rugged field computers: the Trimble Recon® handheld and Trimble Ranger™ handheld.

Choosing software? Trimble's TerraSync™ software or the GPScorrect™ extension for ESRI ArcPad software provides a complete solution from field to office and back. Choose any off-the-shelf GPS field software, or use the GPS Pathfinder Tools Software Development Kit (SDK) to build an application that's customized to your needs.

Productivity and precision

When accuracy is critical for your GIS, the ProXH receiver delivers reliable subfoot performance. Field workers will love the convenience of its compact, cable-free design—and the ability to collect high accuracy data quickly and efficiently. With the GPS Pathfinder ProXH receiver, you don't have to choose between productivity and precision—you can have it all!

GPS Pathfinder ProXH receiver

STANDARD FEATURES

GPS

- Integrated GPS/SBAS¹ receiver and antenna
- H-Star technology for subfoot (30 cm) postprocessed accuracy
- Submeter accuracy in real-time
- EVEREST™ multipath rejection technology
- RTCM input
- NMEA and TSIP protocol support

System

- Integrated GPS receiver, antenna and battery
- Integrated Bluetooth wireless technology
- User replaceable all-day battery
- Wearable GPS receiver with ergonomic belt clip
- Rugged weatherproof housing

Software

- GPS Controller software for mission planning and GPS configuration
- Bluetooth deactivation utility

Accessories

- Power supply with international adapter kit
- Ergonomic belt clip
- Screwthread adaptor for range pole, backpack, or vehicle mounting
- Null modem cable
- User Guide

OPTIONAL FEATURES

Software

- TerraSync software
- Trimble GPScorrect extension for ESRI ArcPad software
- Custom applications built with the GPS Pathfinder Tools Software Development Kit (SDK)
- GPS Pathfinder Office software
- Trimble GPS Analyst extension for ESRI ArcGIS software

Field computers

- Field computer powered by the Windows Mobile® version 6 operating system, Windows Mobile version 5.0 software, or Windows Mobile 2003 software for Pocket PCs, such as:
 - Trimble Ranger handheld
 - Trimble Recon handheld
- Field computer running Windows® desktop operating system

Accessories

- Zephyr antenna kit
- 1 foot pole (for backpack mounting)
- 2 meter range pole
- Hard carry case
- Serial port splitter cable
- GeoBeacon™ receiver
- Backpack
- Range pole bracket
- Magnetic vehicle mount

© 2006–2008, Trimble Navigation Limited. All rights reserved. Trimble, the Globe & Triangle logo, and GPS Pathfinder are trademarks of Trimble Navigation Limited, registered in the United States and in other countries. EVEREST, GeoBeacon, GPS Analyst, GPScorrect, H-Star, ProXH, TerraSync, and Zephyr are trademarks of Trimble Navigation Limited. The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Trimble Navigation Limited is under license. Ranger and Recon are trademarks of Tripod Data Systems Inc., a wholly owned subsidiary of Trimble Navigation Limited. Windows and Windows Mobile are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. All other trademarks are the property of their respective owners. 022501-022G (10/08)

TECHNICAL SPECIFICATIONS

Physical

Integrated GPS receiver, antenna, and battery
Size 10.6 cm x 4.0 cm x 14.6 cm (4.2 in x 1.6 in x 5.75 in)
Weight 0.53 kg (1.16 lb)
Power
Low (GPS only) 0.8 Watts
Normal (GPS and Bluetooth) 1.0 Watt
High (optional Zephyr antenna, GPS, and Bluetooth) 1.6 Watts
Battery User replaceable lithium-ion, chargeable in unit, 13.3 Watt hours

Environmental

Temperature
Operating –20 °C to +60 °C (–4 °F to +140 °F)
Storage –30 °C to +85 °C (–22 °F to +185 °F)
Humidity 99% non-condensing
Casing Wind-driven rain and dust-resistant per IP 54 standard
Drop 1.22 m (4 ft), MIL-STD-810F, Method 516.5, Procedure IV
Vibration Vibration resistant, MIL-STD-810F, Method 514.5, Procedure I
Shock Shock resistant, MIL-STD-810F, Method 516.5, Procedure I

Input/output

Serial Dual port in single DE9
Bluetooth² 2 NMEA/TSIP Serial Port (SPP) services
Interface Power button, 3 status LEDs

GPS

Channels 12 (L1 code and carrier/L2 carrier)³
Integrated real-time SBAS¹
Update rate 1 Hz
Time to first fix 30 seconds (typical)
Protocols TSIP, NMEA (GGA, VTG, GLL, GSA, ZDA, GSV, RMC)

Accuracy (HRMS)⁴ after differential correction

H-Star postprocessed⁵
With internal antenna 30 cm
With optional Zephyr antenna 20 cm
Code postprocessed Submeter
Carrier postprocessed⁶
With 20 minutes tracking satellites 10 cm
With 45 minutes tracking satellites 1 cm
Real-time (SBAS¹ or external RTCM source) Submeter

1 SBAS (Satellite Based Augmentation System). Includes WAAS (Wide Area Augmentation System) available in North America only. And EGNOS (European Geostationary Navigation Overlay System) available in Europe only.

2 Bluetooth type approvals are country specific. The GPS Pathfinder ProXH receiver has Bluetooth approval in the U.S. and EU. For other countries please consult your local Distributor.

3 L2 capability requires purchase of the optional Zephyr antenna kit.

4 Horizontal Root Mean Squared accuracy. Requires data to be collected with minimum of 4 satellites, maximum PDOP of 6, minimum SNR of 39 dBHz, minimum elevation of 15 degrees, and reasonable multipath conditions. Ionospheric conditions, multipath signals or obstruction of the sky by buildings or heavy tree canopy may degrade precision by interfering with signal reception. Accuracy varies with proximity to base station by +1 ppm for postprocessing and real-time.

5 Requires H-Star data to be collected for up to 2 minutes. Requires a minimum of three good quality dual frequency reference stations within 200 km, or one good quality dual frequency reference station within 80 km. With one reference station accuracy degrades at +1 ppm beyond 80 km.

6 Accuracy varies with proximity to base station by +5ppm. 45 minute carrier capability applies only to GPS Pathfinder Office software.

Specifications subject to change without notice.



CompassTools

Map it, Design it, Find it, Build it, Track it

"Dedicated to GIS since 1994"

Sales, Support, Authorized Repair, Rental, Training

CO, NM, AZ, MN, SD, ND
(800) 728-5066 (toll free) www.compasstoolsinc.com

NORTH & SOUTH AMERICA

Trimble Navigation Limited
10355 Westmoor Drive
Suite #100
Westminster, CO 80021
USA
+1-720-587-4574 Phone
+1-720-587-4878 Fax

EUROPE, AFRICA & MIDDLE EAST

Trimble GmbH
Am Prime Parc 11
65479 Raunheim
GERMANY
+49-6142-2100-0 Phone
+49-6142-2100-550 Fax

ASIA-PACIFIC

Trimble Navigation
Singapore PTE Limited
80 Marine Parade Road
#22-06 Parkway Parade
Singapore, 449269
SINGAPORE
+65-6348-2212 Phone
+65-6348-2232 Fax



www.trimble.com
store.trimble.com